



# TONY 8700 V



5  
STAGE

75,3<sub>hp</sub>



SCAN ME



HYDROSTATIC  
TRANSMISSION

40  
Km



EXG  
MAXIMUM  
PROTECTION  
GUARANTEE

Frame	Frame with oscillating front axle • 55° steering front wheels • Four-wheel drive (front drive wheels can be disengaged)
Engine Type	DEUTZ - 4 Cylinders - 16 Valves - Turbo Intercooler Stage 5 - Common rail - 2900 cc Power 55,4 kW / 75,3 cv - 1400 to 2200 rpm Max Torque 375 Nm a 1400 rpm
Transmission	MECHANICAL - HYDROSTATIC HYBRID
Power Take-off	Rear, independent 2-speed 540 and 540E rpm
Hydraulic system	PLUS hydraulic system comprised of: 9 independent double-acting hydraulic couplers with programmable functions and operating parameters. Variable displacement pump and auxiliary pumps for high flow rates at low engine revs.
Rear Lift	Adaptive rear lift - Hydraulically controlled lateral movement and oscillation of lift unit - Lifting capacity 2700 kg - Fixed EU-type rear tow hitch SLIDER (ex cat. C)
Brakes	Hydraulic service brake system with oil-immersed double discs, pedal operated and acting on rear wheels, integral braking system with automatic engagement of four-wheel drive. Oil-immersed multidisc parking brake with automatic engagement system.
Weight	With Cab. (Kg): 2900÷3066

### DIMENSIONS WITH STANDARD WHEELS: FRONT 240/70 R16 REAR 320/70 R20

	A	B	C	D	G	H	I	L
8700	3555÷3910	590	2095	870÷930	270	2320	2140	1120

