



**51.5<sub>hp</sub>**



SCAN ME



TRANSMISSION  
16+16  
SYNCH. INVERTER



EXG  
MAXIMUM  
PROTECTION  
GUARANTEE

**5  
STAGE**



<b>Frame</b>	ACTIO™ integral oscillating frame • RGS™ reversible drive system • Steering wheels • Four equal-size driving wheels • Horizontal rear final drives	
<b>Engine type</b>	5800   YANMAR - Direct injection diesel common rail Turbo 4 Cylinders - 16 Valves - 2091 cc Stage 5 - Power 37.9 kW / 51.5 hp - 2600 rpm Max torque 170 Nm at 1690 rpm	
<b>Transmission</b>	S90: 32 speed synchronised gearbox: 16 FWD + 16 REV with synchronised shuttle	
<b>Power take-off</b>	Rear, independent 540/540E rpm with progressive electro-hydraulic engagement; synchronised groundspeed	
<b>Hydraulic system</b>	Load sensing. Rear auxiliary hydraulic system with 1 double-acting remote valve with float and 1 oil return (3 rear hydraulic couplers). Pump capacity 37lt/min	
<b>Rear power lift</b>	Oscillating lift arms and lateral stabilizer bars, Cat. 1 - Lifting capacity (Kg): 2190 - Front tow hook; Category "C" height-adjustable rear tow hook	
<b>Brakes</b>	Rear service brakes: oil-immersed dual discs with hydraulic control, steering brakes - Combined parking brake: belt brake on the transmission and acting on the brake blocks with integrated mechanical superbake system.	
<b>Weight</b>	With roll bar (Kg): 1800 to 2015	With RedCab (Kg): 1950 to 2165

**DIMENSIONS WITH STANDARD WHEELS: 7.50x16**

	A	B	C	D	E	F	G	H	I	L
TRX 5800	3360 to 3615	1210	1485	665 to 920	1149	2223	261	2169	-	1240

